

# Anhydrous Applicator



## Specifications

**Model TB42 • TB47 • TB52 • TB60**

	TB42 • TB47	TB52	TB60
Working widths	42', 47'	52'	60'
Wings	Double Fold	Double Fold	Triple Fold
Mainframe & wing tubing	4 x 6 x 3/8 Tubing	4 x 6 x 3/8 Tubing	4 x 6 x 3/8 Tubing
A-frame tubing	4 x 8 x 3/8 Tubing	4 x 8 x 3/8 Tubing	4 x 8 x 3/8 Tubing
Transport Height	13' 10"	13' 10"	13' 10"
Transport Width	20'	20'	20'
Mainframe wheels walking tandems	(4) 12.5L 15" 8-bolt	(4) 12.5L 15" 8-bolt	(4) 12.5L 15" 8-bolt
Secondary lift wheels walking tandems	(4) 9.5L 15" 6-bolt	(4) 9.5L 15" 6-bolt	(4) 9.5L 15" 6-bolt
Gauge wheel	Pin Adjust	Hydraulic	Pin Adjust
Rear hitch	Telescopic + Swings right & left	Telescopic + Swings right & left	Telescopic + Swings right & left
Combo single & double clevis	Yes	Yes	Yes
Lift System (3,000 psi), Synchronized	4 Cylinder Lift	6 Cylinder Lift	6 Cylinder Lift
Flashing & warning tail lamps	Yes	Yes	Yes
Number of Shanks	42'--15" Centers = 33 shanks 42'--30" Centers = 17 shanks 47'--15" Centers = 37 shanks 47'--30" Centers = 19 shanks	52'--15" Centers = 41 shanks 52'--30" Centers = 21 shanks	60'--15" Centers = 49 shanks 60'--30" Centers = 25 shanks