

DRY TENDER TRAILER

Built To Haul, Built To Last



Tender sold separately



Optional third axle



Standard Equipment

Frame Length	25' or 34' Lower Deck; 11' Upper Deck
Frame Width	39'
Frame	I-Beam; I-Beam Fifth Wheel
Capacity	45,000 GVWR
Axle	(1) 22,500 lb. Oil Bath Heavy Duty Axle with Anti Lock Air Brakes with Automatic Slack Adjusters and Park Brake
Axle	(1) 22,500 lb. Oil Bath Heavy Duty Axle with Air Brakes with Automatic Slack Adjusters and Park Brake
Suspension	Hutch Suspension 9700 3-point
Wheels	(8) 22.5" x 8.25" Budd Style Dual Wheel with 10 on 11.25"
Tires	(8) 255/70R-22.5 Tire, New
Jack	Holland Landing Gear Set 2-Speed Jack, Handle and Crosspipe
Hitch	King Pin, 48" Ground Clearance, 2" SAE with 3/8" Bolster Plate
Lighting	DOT Approved, All Sealed Rubber Mounted
Finish	Powder Coat-Black; Prepped, Bead Blasted and Acid Washed
Other	Mud Flaps Reflector Tape

Ask dealer about available options.

Behnke Enterprises, Inc. reserves the right to make changes without notification.



Manufactured by:

BEHNKE ENTERPRISES, INC.
 800 Ninth Ave. NW | Farley, Iowa 52046
 Ph. 563-744-3246 | Fax 563-744-9066
www.behnkeenterprises.com